

Colour Enhancing Sealer



Colour Sealer



1 Litre



Active Compound Resin

Colour Enhancing Stain Protection For Natural Stone & Tiles

Marble, Limestone, Travertine, Granite, Quarry Tile, Slate And Stone.

Gives excellent protection against both oil and water based stains

Deepen colour of stone

Protects and seals both indoor and outdoor surfaces

Aids maintenance and makes it easy to clean your floor



What Will it Seal

Colour enhancing sealer is ideal to seal, protect and enhance the colour and natural beauty of your natural stone and give great stain protection on Marble, Limestone, Travertine, Granite, Quarry Tiles and any low absorbency stones. Using The Tile Master Active Compound Resin Protection System, your tiles are protected from dirt, grime and daily food spills with our invisible and breathable sealer. **Warning : does not protect stone from acid or chemical damage, surface wear or scratching. Creates a permanent colour change which can not be removed once applied.**

Where to use

Perfect for use on your floors, walls, wet rooms & countertops in your Kitchen, Hall Way, Bathroom, Patios, Swimming Pools or anywhere around your home or garden to protect polished stone.

Benefits

Enhances the natural colours of the stone and tile

Gives excellent protection against both oil and water based stains

Protects and seals both indoor and covered outdoor surfaces

Easy to apply and Ready to USE

Aids maintenance and makes it easy to clean your floor

How to Use & Apply

- 1) Always TEST PRODUCT ON SMALL AREA FIRST. Allow to cure for 24 hrs and check for desired results, colour change and protection level.
- 2) Check that area is dry, clean and free of all residue and previous treatments.
- 3) Evenly apply 1 generous coat of the sealer to saturate the tile. The tile should hold a wet or glass like look for about 5 seconds. Apply more sealer if required to achieve this.
- 4) After 10 minutes or before the sealer dries on the surface, remove and buff off any excess sealer using clean and dry white towels or cloths. Work the product into the surface using circular motions to achieve deep penetration of the sealer. To remove stubborn residue, simply reactivate using a clean cloth, slightly wet with the sealer.
- 5) For highly absorbent stone apply a light second coat after 24 hours, using steps 3 and 4 as above.
- 6) The floor is fine for light foot traffic in socks and slippers after 4 hours from final coat. Allow 48 hours before wetting the floor or contact with water or stains

Coverage Rates Per 1 Litre per coat

Polished Stone - 20 - 25 sqm

Honed Natural Stone - 12 - 15 sqm

Floor preservation and ongoing Maintenance

Surfaces treated with the sealer should be maintained with Tile Master Cleaner No2, diluted at 1-50, (1 cap in 5 litres of Water)

WARNING; Ensure the sealer is stored in a cool dry place and kept away from heat at all times. This sealer is flammable. Ensure area is well ventilated and wear suitable clothing and gloves. Exposure may cause dry or cracked skin. Harmful if swallowed. Can irritate eyes. Replace lid after each use. Keep out of reach from children and pets. Do Not pour down drains. Get medical advice if swallowed.

1 Litres



Tile Master Global Limited
22 Village Square, Bramhall Centre
Stockport, Cheshire, SK7 1AW
www.thetilemaster.co.uk