



# MATERIAL SAFETY DATA SHEETS TileMaster – Satin Wax Dressing (Water)

Section 1 – Product Identification	
Product name	TileMaster Satin Wax Dressing (Water)
Product type	Liquid
Product description	Water-based solution to dressing marble,
	granite, porous stone
Prepared by	TileMaster Global Limited, Unit 11 / 12 Shepley
	Land Ind Est, Hawk Green, Stockport, SK6 7JW
	Tel: 0161 444 0377 email:
	info@thetilemaster.co
Compilation date	18.10.2015 – Revision No.3

#### Section 2 – Hazards Identification

#### 2.1

Classification of the substance according to Regulation EC n. 1272/2008

The product is not classified as dangerous -

Irritant Xi; H315, H319

Dangers for human health: Skin and eyes irritating See section 16 for the complete text of sentence H

See section 11 for additional information on health effects

Hazardous indications: H305 May be harmful if swallowed and if penetrating in breathing ways.

EUH066 repeated exposure may cause skin dryness and cracks.

Prudence recommendations:

P101 Keep far from the reach of children

P210 keep far from heating sources/sparks/free flames. Do not smoke

P280 Wear gloves/protective clothes/protect eyes/face P301-P310 IN CASE OF INGESTION: immediately call a doctor P501 Collect the product/container according to Directives.

P207 use only outside or in a well airy ambient.

Indications on precautions:

Prevention: Wear protective gloves

Protection for eyes and face.

Do not eat, drink or smoke during use.

Wash hands well after use.

Disposal: Do not waste residues in the environment

#### 2.2

Label indications:



Danger labelling in compliance with (CE) 1272/2008 (CLP) Regulation and following modifications and adjustments

Danger: Irritant



T +44 (0)161 444 0377 E info@thetilemaster.co.uk www.thetilemaster.co.uk

Risk: H315 causes skin irritation Risk: H319 causes eye irritation

Safety: S24/S25 avoid contact with eyes and skin

S36/S37/S39 wear suitable protective clothes and gloves to protect

eyes/face

# Section 3 – Composition / Information on the ingredients

3.1

Substances: Not applicable

3.2

Mixtures: No dangerous component according to Regulations. (CE) no. 1907/2006 and (CE)

No.453/2010

# Section 4 – First Aid Measures

#### 4.1

First aid measured description:

In case of contact with the skin: Remove dirty shoes and clothes

then safely dispose them. Wash the area with soap and water. Immediately call a doctor in case of irritation, swelling or redness persist. In case of contact with the eyes: Rinse well with water. Call the specialist doctor or local hospital if irritation persists.

4.2

Main symptoms and effects both acute and delayed, see chapter 11:

Skin contact: Redness, irritations Eyes contact: Eyes irritation

4.3

Indication on the eventual necessity of contacting a doctor and special treatments - Follow doctor's instructions.

## Section 5 – Anti-Fire Measures

#### 5.1

The product is not flammable

## Section 6 – Accidental Release Measures

#### 6.1

Personal equipment, protective clothing and emergency procedures:

Wear suitable protective clothes

6.2

Precautions for the environment:

Do not pour down drains

6.3

Methods and materials to collect and clean:

Collect with absorbent materials like sand, sawdust and dispose according to proper rules





#### Section 7 - Handling and Storage

7.1

Precautions for safe handle:

Wear gloves, apron, mask and boots.

7.2

Safe warehouse:

Keep container well sealed in a dry place; protect from freeze and avoid temperatures higher than  $40^{\circ}$ C. Do not keep in warehouse together with

acids and strong basis.

7.3

Specific end uses:

Anti-stain treatments

#### Section 8 – Exposure Control and Protection

#### 8.1

Since the use of suitable technical measures should be first than personal protection equipment, it's necessary to ensure a proper ventilation through the use of a good aspiration device or the polluted air discharge. If these operations do not keep product concentration under minimum exposure values, it will be necessary to wear a suitable breathing apparatus protection. During use, refer to danger label for more details. Personal protective clothes must be in compliance with the rules here below indicated:

**Hands Protection** 

Protect hands using working gloves, II category. (ref. Directive 89/686/CEE and Rule EN 374) like: PVC, neoprene, nitrile or equivalent.

The final choice of the gloves must consider: degradation, breaking time and permeability. In case of mixtures the gloves resistance must be checked before using, it is not foreseeable. Gloves have a wear and tear term that depends on exposure time.

Eyes Protection Wear sealing protective mask (ref. Rule EN 166)

Skin Protection Wear long sleeves working clothes and shoes for professional use, II category. (ref. Directive CEE and EN 344 rule). Wash with plenty of water after taking protective clothes off. Breathing Protection

In case of overcoming of the limit value of one or more substances present in the product, wear a mask with filter A type or the universal type, whose class (1,2 or 3) will be chosen according to the use. (ref. EN 141 Rule). The use of breathing apparatus protections, like mask with filter for organic vapors and powders/fog, it's compulsory in absence of technical measures to limit the worker exposure. The protection given by the mask is limited anyway. If the substance is odourless or in case of emergency (unknown time of exposure or the oxygen level in the ambient is lower than 17%) wear a compressed air auto-breather at open circuit (ref. Rule EN 137) or a respirator with external air outlet for the use with whole mask, semi-mask or nozzle. (Ref. Rule EN 138). If there's the risk to get squirts or sprinkles due to the type of work performed, it's necessary to foresee a suitable mucous protection (mouth, nose, eyes) in order to avoid accidental absorptions.

### 8.2

Limits of exposure:

No substance at exposure limit

### 8.3

Exposure control, Technical controls:



T +44 (0)161 444 0377 E info@thetilemaster.co.uk www.thetilemaster.co.uk

Handle in well ventilated areas

8.4

Individual protection:

Wear gloves and mask, in normal use conditions no vapors is generated

8.5

Environmental protection:

Avoid discharge in sewers

# Section 9 – Chemical and Physical Propoerties

9.1

Status:

Liquid

Color:

White

Odor:

Typical

Smelling threshold:

No data available

pH:

Between 6 and 8

Boiling point:

105°C approx.

Fusion point:

not applicable

Flashing point:

Not applicable

Ignition temperature:

not determined

Vapors:

Not determined

Viscosity:

Approx. 30 mPa s

Solubility:

Soluble in water

# Section 10 – Stability and Reactivity

10.1

Reactivity:

No dangerous reaction in normal conditions of use

10.2

Chemical stability:

The product is stable

10.3

Possible dangerous reactions:

No dangerous reactions detected

10.4



T +44 (0)161 444 0377 E info@thetilemaster.co.uk www.thetilemaster.co.uk

Conditions to avoid:

Contact with acids and strong basis

10.5

Hazardous decomposition products:

Decomposition starts at temperatures higher than 150°C; in normal use conditions no decomposition is detected

#### Section 11 – Toxicological Infomation

Acute inhalation toxicity:

No relevant data

Acute oral toxicity:

LD50 ratto > 5.110 mg/kg

Contact with the skin:

May cause irritation

Contact with the eyes:

May cause eyes irritation

Ingestion:

No effect on human health linked to the product ingestion has been

detected. Use the product according to the instruction.

Ingestion can cause:

Gastrointestinal irritation. Symptoms: pain, vomit, nausea and abdomen

pain.

Additional toxic information:

No particular negative effect has been detected.

### Section 12 – Ecological Information

There's no information on the product, so use it according to good working procedures, do not waste it in the environment. Absolutely avoid to waste product in the ground or drains. Call authorized companies if the product reaches water drains or in case of ground or flora pollution. Follow all the measures to reduce at the minimum level the effects on water drains.

#### 12.1

**Toxicity Information:** 

Not available

12.2

Persistence and degradability Information:

Not available

12.3

Potential bio-accumulative Information:

Not available

12.4

Mobility in the ground Information:

Not available

12.5

Results of the PBT and vPvB evaluation Information:

Not available



T +44 (0)161 444 0377 E info@thetilemaster.co.uk www.thetilemaster.co.uk

12.6

Additional effects Information:

Not available

## Section 13 – Disposal Considerations

13.1

Waste Handling:

Re-use, if possible the product. Product residues must be regarded as special dangerous waste. Waste danger that contain this product must be evaluated

on the basis of current rules.

Disposal:

Must be performed by company authorized to waste handling, according to national and local current rules. Polluted Packages, Polluted packages must be recovered or wasted in compliance with National rules concerning waste management.

### **Section 14 - Transport**

14.1

UN Nr.:

not ruled

14.2

ADR Class:

not ruled

14.3

**IMO Class:** 

not ruled

14.4

**ICAO Class:** 

not ruled

# Section 15 – Regulatory Information

Regulation on health, safety and environment specific for the substance

Regulation CE n. 1907/2006 (Reach), Annex XIV list of substances subject to

authorization

Substances SVHC: none Annex XVII: none

## Section 16 – Other Information

16.1

Classification according to Regulation CE 1272/2008

Hazard indications

Flam. Liq.2 Flammable liquid, cat. 2

Acute tox.3 High toxicity, cat. 3

STOT SE 1 Specific toxicity for target - single exposure, Cat. 1

Flam.Liq.3 Flammable liquid, cat.3

**STOT SE 3** Specific toxicity for target-single exposure, Cat.3



T +44 (0)161 444 0377 E info@thetilemaster.co.uk www.thetilemaster.co.uk

Carc. 1B Cancerougenicity, CAT 1 B

Muta, 1B Mutagenicity on stem cells, cat. 1 B

**Asp. Tox.1** Danger in case of aspiration, cat. 1

Acute tox.4 High toxicity, cat. 4

STOT RE 1 Specific toxicity for target - repeated exposure, cat. 1

Eye Irrit. 2 Eyes irritation, cat.2

Aquatic Acute 1 Dangerous for fish fauna, high toxicity, cat.1

Aquatic Chronic 1 Dangerous for fish fauna, high toxicity, cat.1

**H226** Liquid and flammable vapours

H305 may be harmful if swallowed and by penetrating breathing ways.

H315 causes skin irritation

**H319** causes severe eye irritation

EUH066 Continuous exposure may cause skin dryness and cracks.

Text of risk sentences (R) is indicated at section 2-3 of this data sheet.

R10 flammable

R11 easily flammable

R 23/24/25 toxic by inhalation, skin contact, ingestion

**R36** eyes irritating

R48/25 toxic: serious healthy damages in

Case of long exposure by ingestion.

R50/53 high toxic for aquatic organism,

At long term it may cause negative effects for fish fauna

**R65** harmful: if swallowed could cause serious damage to lungs.

**R66** continuous exposure may cause skin dryness and cracks.

**R67** vapours inhalation may cause sleepiness and giddiness.

**R68** possibility of non-reversible effects.

General Bibliography

- 1. Directive 1999/45/CE and following modifications
- 2. Directive 67/548/CEE and following modifications
- 3. Regulation (CE) 1907/2006 of European Parliament (REACH)
- 4. Regulation (CE) 790/2009 of European Parliament (I Atp. CLP)
- 5. Regulation (CE) 453/2010 of European Parliament
- 6. The Merck Index Ed. 10
- 7. Handling Chemical Safety
- 8. Niosh- Regestry of Toxic Effects of Chemicals Substances
- 9. INRS Fiche Toxicologique
- 10. Patty- Industrial Hygiene and Toxicology
- 11. N.I. Sax. Dangerous properties of Industrial Materials 7 Ed. 1989

## **USER'S NOTES:**

The information herein contained have been draught on the basis of available knowledge upon data sheet version. The user must make sure of the suitability and completeness of the information referring to the specific use of the product. Do not read this document as warranty of any specific property of the product. Since the use of the product is not under our direct control, it's the user's liability respect current rules in terms of hygiene and safety. We are not held liable for unproper use.