



## GENERAL DESCRIPTION

Junckers PreLak is a fast drying, water-based primer for use on wooden floors in commercial, residential or sports areas.

Protective coats with one of Junckers water based floor lacquers have to be applied after priming.

## PRODUCT DESCRIPTION

**Product:** Water-based acrylic primer.

**Package sizes:** 5 litre and 10 litre.

**Appearance:** Creamy/milky. Dries up to a clear film.

## TECHNICAL DATA

**Coverage:** 8 m<sup>2</sup> per litre.

**Before application:** Stir or shake the lacquer well before use.

**Application tools:** Short hair roller.  
Don't apply by pouring out the lacquer directly on the floor.

**Substrate temperature:** Minimum 15° C and maximum 25° C.

**Dilution:** Delivered ready for use. Dilution is not recommended.

**Drying time at 20° C and 50 % RH:**  
Approx. 1-2 hours.

**RH:**  
Water-based products have a certain gluing effect and are therefore only recommended to be used in rooms with a stable humidity. The difference between highest and lowest RH must not fluctuate more than 30 % during the year.

**Cleaning of tools:** Soap and water immediately after use.

**Storage:** Lasts for 1 year if unopened and stored at 20° C. Not to be exposed to temperatures below 5° C.

## SYSTEM RECOMMENDATIONS

### High traffic areas:

1 coat Junckers PreLak 8m<sup>2</sup>/litre + 2 coats Junckers HP Commercial 10m<sup>2</sup>/litre or  
1 coat Junckers PreLak 8 m<sup>2</sup>/litre. + 2 coats Junckers Strong Premium 10m<sup>2</sup>/litre or  
1 coat Junckers PreLak 8 m<sup>2</sup>/litre. + 2 coats Junckers Strong 10m<sup>2</sup>/litre.

### Low traffic areas:

1 coat Junckers PreLak 8 m<sup>2</sup>/litre + 2 coats Junckers ProFinsh 10 m<sup>2</sup>/litre

### Sport areas:

1 coat Junckers PreLak 8 m<sup>2</sup>/litre + 2 coats Junckers HP Sport 10-12 m<sup>2</sup>/litre

## DIRECTION FOR USE

### Untreated/sanded floors:

The surface should be clean, dry and free from dust, wax, grease, polish etc.. Machine sand the surface to remove dirt and irregularities. Vacuum thoroughly and wipe off with a well wrung cloth and clean water.

The final sanding, before applying Junckers PreLak should be carried out by using sandpaper grit 120-150.

Apply one coat of Junckers PreLak using a clean, shorthaired roller or applicator. Do not apply by spraying. When the primer is dry, sand with sandpaper grit 150-180 or a black screening pad. Then finish the floor with one of Junckers recommended floor lacquers.

### Previously sealed floors:

Machine sand before applying Junckers PreLak. Use grit 24-36 to strip previous coats. Then remove abrasion marks with grit 60-80. Finally, use grit 120-150 to obtain a completely smooth surface.

Vacuum sanding dust and wipe off with a well wrung cloth and clean water. Prime the floor as described under "Untreated/ sanded floors".

## PRECAUTIONARY MEASURES

Before using the product, read the label on the container carefully and observe the recommended precautionary measures. See Material Safety Data Sheet for detailed information.

## FURTHER INFORMATION

### Products:

F 4.2 - Junckers ProFinish  
F 5.1 - Junckers Strong  
F 5.9 - Junckers Strong Premium  
F 8.2 - Junckers HP Sport  
F 8.5 - Junckers HP Commercial